

SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Community Playthings

10 Hellbrook Lane PO Box 2, Ulster Park, New York 12487, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

Indoor Advantage™ Gold

Indoor Air Quality Certified to SCS-105 v4.2

Conforms to the ANSI/BIFMA Furniture Emissions Standard (M7.1/X7.1-2011 R2021) and ANSI/BIFMA e.3-2019 (Credits 7.6.1, 7.6.2, 7.6.3) and CDPH/EHLB Standard Method (CA 01350) v1.2-2017 (effective January, 2017) for low emissions criteria by modified modeling parameters per AHSRAE 62.1-2010, as noted in the certificate addendum. ¹Modeled as Nursery Room Furniture System.

NURSERY ROOM FURNITURE SYSTEM MODELING PARAMETERS : Room Volume: 154 m³; Adjusted Outdoor Air Flow Rate†: 145 m³/hr; Total Occupancy‡: 15; Total Seating Units: 15; Total Sleeping Units: 15 † The adjusted air flow rate was based on based on ASHRAE 62.1-2010, Table 6-1, for classrooms occupied by pupils, ages 0-4. The minimum ventilation requirement is 5 L/s-person (10 cfm/person) and 0.9 L/s-m²floor area (0.12cfm/ft²). The code minimum total flow rate of outdoor air is then 461m³h⁻¹. This produces a ventilation rate of 2.8 h⁻¹ for occupied hours. For use in this method, the average ventilation over a 168-h week was calculated, assuming 40 hours of operation at 405 m³h⁻¹ and 128 hours of operation with ventilation of only 0.2 h⁻¹ due to infiltration. This yields an average ventilation rate of 0.82 h⁻¹ and an average flow rate of 145m³h⁻¹; ‡ The number of occupants was based on the default occupancy from ASHRAE 62.1-2010 for Educational Environments for daycare through age 4, 25 occupants per 100 m².

Registration # SCS-IAQ-03371

Valid from: November 01, 2024 to July 31, 2025



A handwritten signature in black ink, appearing to read 'D. Phillips'.

Diana Kirsanova Phillips, Chief Assurance Officer, SCS Global Services

Certification Addendum Community Playthings

Certification: Registration # SCS-IAQ-03371 | Valid from: November 01, 2024 to July 31, 2025

Addendum **Indoor Advantage™ Gold**

Conformance: Indoor Air Quality Certified to SCS-105 v4.2

Conforms to the ANSI/BIFMA Furniture Emissions Standard (M7.1/X7.1-2011 R2021) and ANSI/BIFMA e.3-2019 (Credits 7.6.1, 7.6.2, 7.6.3) and CDPH/EHLB Standard Method (CA 01350) v1.2-2017 (effective January, 2017) for low emissions criteria by modified modeling parameters per AHSRAE 62.1-2010, as noted in the certificate addendum. *Modeled as Nursery Room Furniture System.

NURSERY ROOM FURNITURE SYSTEM MODELING PARAMETERS : Room Volume: 154 m³; Adjusted Outdoor Air Flow Rate†: 145 m³/hr; Total Occupancy‡: 15; Total Seating Units: 15; Total Sleeping Units: 15 † The adjusted air flow rate was based on based on ASHRAE 62.1-2010, Table 6-1, for classrooms occupied by pupils, ages 0-4. The minimum ventilation requirement is 5 L/s-person (10 cfm/person) and 0.9 L/s-m² floor area (0.12cfm/ft²). The code minimum total flow rate of outdoor air is then 461m³h⁻¹. This produces a ventilation rate of 2.8 h⁻¹ for occupied hours. For use in this method, the average ventilation over a 168-h week was calculated, assuming 40 hours of operation at 405 m³h⁻¹ and 128 hours of operation with ventilation of only 0.2 h⁻¹ due to infiltration. This yields an average ventilation rate of 0.82 h⁻¹ and an average flow rate of 145m³h⁻¹; ‡ The number of occupants was based on the default occupancy from ASHRAE 62.1-2010 for Educational Environments for daycare through age 4, 25 occupants per 100 m².

Products:

Crib Systems/ Sleep Systems:

Cribs: Crib Mattress G11; Crib Sheet Blue G13; Crib Sheet White G14; Community Crib G302; BackSafe Crib G304; BackSafe Evacuation Crib G307; Community Evacuation Crib G309

Rest Mats: Rest Mat M65; Rest Mat Sheet S12; Rest Time Blanket S15

Cots: Cot Label Holder M160; Toddler Cot M161; Toddler Cot Sheet M166; Full-Size Cot M162; Full-Size Cot Sheet M167; Toddler Cot Dolly M171; Full-Size Cot Dolly M172